



## Case erectors **BEM200** **BEM200xs**

The BEM 200 and BEM200xs automatic case erectors are equipped a gravity storage of folded boxes, a system for opening them, close the bottom flaps and seal the bottom, freeing the box mounted with the bottom closed and prepared to introduce products vertically. Easy to operate and adjust, they integrate a touch screen to simplify the user's work. Maximum precision in every movement to ensure high productivity and quality.

MODEL		BEM 200	BEM 200xs
Max. production	boxes/ min	12	11
Max. box measures (external measures)	L mm	530	300
	A mm	400	250
	H mm	600	370
Min. box measures (external measures)	L mm	250	150
	A mm	150	120
	H mm	225	190
Types of admissible boxes		RSC, HSC, FEFCO 0200/0201	RSC, HSC, FEFCO 0200/0201
Lower closures available		Adhesive tape, hot melt	Adhesive tape, hot melt
<b>TECHNICAL DATA</b>			
Weight	kg	400	250
Dimensions	L mm	3510	2375
	A mm	1950	1956
	H mm	1460	1210
Gravity storage capacity	boxes	120	120
Work height	mm	630-750	630-750
<b>SERVICE</b>			
Electrical voltage		230 V II+T	230 V II+T
Installed power	kW	0,5	0,5
Power consumption	kW/h	0,4	0,4
Pneumatic pressure	bar	6	6
Air consumption	l/cycle	29	25
<b>OPTIONS</b>			
Powered warehouse		○	○
Stainless steel		○	○